EURO-LOCKS
LOCKING SYSTEMS FOR INDUSTRY

Euro-Locks Sp. z o. o. ul. Pawła 29 41-708 Ruda Śląska

+48 (32) 344-78-70, -82, -84

Fax: +48 (032) 344-78-74

Nimbus RFID Digital Combination Lock 3963

Product Description

The Nimbus RFID digital lock provides contactless locking in the same sleek, slimline style and footprint as the Nimbus digital combination lock. Compatible with ISO14443A RFID standards, Nimbus RFID incorporates a membrane touchpad for ease of programming which can also be used to override the lock when required.

- Choice of RFID card or keypad use
- Compatible with ISO14443A RFID standards including Legic-Advant-Protocol and Mifare-Protocols
- **Standard finish**: Black, silver or white; Chrome and brushed nickel finishes available on request
- **Fitting options**: Surface mount or semi-flush fit fitting (maximum 20mm protrusion)
- **Fixing options**:
- Vertical, left and right hand
- Two or three-point fixing
- **User codes**: 8-digit master code; 6-digit sub-master code; 4 or 6-digit user code
- **User modes**: Public mode, private mode, technician mode or RAS
- **Spindle length**: 20mm or 24mm
- Steel override key (2-keys supplied per 50 locks)
- Wide variety of cams
- LED indicator lights
- Optional audible keypad
- Battery condition indicator
- 2 x AAA batteries (included)
- Up to 50,000 cycles per pair of batteries
- Multiple incorrect code timed lock-out protection
- High, normal or low speed detection mode

Programming features

- Change master card
- Add user card (private mode only)
- Set private mode
- Set public mode
- Set audio

Optional features

- One or two time RAS mode
- Alternative colours
- Pre-programmed modes and codes
- Customised logo

Options

Product Code	Body Width	Body Height	Body Depth
3963	41	140	24.75